

IL-CFFD SERIES

IRONLINK® COMPACT FORM FACTOR GPU-READY WORKSTATION

PRODUCT OVERVIEW

The IL-CFFD is powered by the latest Intel® Core[™] Ultra processors for fast and stable performance, ideal for client viewing station applications.

This unit packs the latest workstation features into a compact design, with up to 64GB of RAM and 8TB of SSD storage. Despite its compact size, the IL-CFFD supports a 75W discreet GPU.



KEY FEATURES

•

Up to 8TB of Raw Storage



GPU-Ready



Intel[®] Core[™] Ultra Processor



5-Year ProSupport Plus NBD On-Site with KYHD





Images displayed are for general reference only and may differ based on build. Product specifications are provided for informational purposes only, and are subject to change, correction, or revision without notice. It is the customer's responsibility to validate product specifications prior to purchase or installation, and to ensure that those specifications are suitable for a particular use. Please refer to velasea.com or contact your sales representative for the latest IronLink[®] products, specs, and upcoming releases. Intel[®], Core[™], Xeon[®], and the Intel[®] logo are trademarks of Intel Corporation. Microsoft[®] and Windows[®] are trademarks of Microsoft Corporation. Ubuntu[®] and the Ubuntu[®] logo are trademarks of Canonical Corporation. NVIDIA[®] and the NVIDIA[®] logo are trademarks of NVIDIA Corporation.



IL-CFFD SERIES

IRONLINK® COMPACT FORM FACTOR GPU-READY WORKSTATION

SYSTEM

Operating System: Windows[®] 11 Pro Windows[®] 10/11 IoT Enterprise Ubuntu[®] Linux 20/22.04

Supported CPU: (1) Intel® Core[™] Ultra

Memory Configuration: (2) SODIMM Slots Up to 64GB DDR5 Non-ECC

Embedded Networking: (1) RJ45 1GbE Port (1) RJ45 5GbE Port

Expansion Slots: N/A

GPU Support: Up to (1) SFF Double Wide GPU

Security Module: Trusted Platform Module (TPM) 2.0

MECHANICAL

Form Factor: Compact Tower

Power Supply: (1) 280W External

Environmental: Operating Temperature: 32°F ~ 95°F (0°C ~ 35°C)

Non-Operating Temperature: -40°F - 149°F (-40°C - 65°C)

Operating Rel. Humidity: 20% – 80% (non-condensing)

Non-Operating Rel. Humidity: 5% – 95% (non-condensing)

Dimensions (WxDxH): 3.12" x 7.00" x 8.11" (79.3 mm x 178 mm x 206 mm)

Weight: 5.6 lb (2.55 kg)

Warranty: 5-Year ProSupport Plus NBD On-Site with KYHD

STORAGE + PORTS

Drive Bays: N/A

M.2 Slots: (2) M.2 slots (2230/2280) (1) M.2 slot for Wi-Fi/Bluetooth Card (2230)

I/O Ports: FRONT: (2) USB 3.2 (1) USB 3.2, Type-C

REAR: (4) USB 3.2 (1) USB 3.2, Type-C

Video Outputs: (3) DisplayPort

Images displayed are for general reference only and may differ based on build. Product specifications are provided for informational purposes only, and are subject to change, correction, or revision without notice. It is the customer's responsibility to validate product specifications prior to purchase or installation, and to ensure that those specifications are suitable for a particular use. Please refer to velasea.com or contact your sales representative for the latest IronLink® products, specs, and upcoming releases. Intel®, Core", Xeon®, and the Intel® logo are trademarks of Intel Corporation. Microsoft® and Windows® are trademarks of Microsoft Corporation. Ubuntu® and the Ubuntu® logo are trademarks of Canonical Corporation. NVIDIA® and the NVIDIA® logo are trademarks of NVIDIA Corporation.