

IL-SFFD-M SERIES

IRONLINK® SMALL FORM FACTOR AI NVR FOR MILESTONE

PRODUCT OVERVIEW

The IL-SFFD-M is an AI-enhanced video surveillance appliance purpose-built for Milestone XProtect[®]. Powered by the latest 14th Gen Intel[®] Core[™] processor and the Hailo-8 Inferencing Module for fast and stable performance, this system is capable of 20+ streams running 40 basic analytics. This unit packs the latest AI NVR features into a compact design, with up to 64GB of RAM, 4TB of SSD storage, and 24TB of HDD storage − all in a box smaller than a foot deep. More than an NVR, these appliances offer a low total cost of ownership and leverage Canopy Cloud RMM at no extra cost for remote device management that significantly reduces truck rolls to customer sites, saving time and money.













KEY FEATURES



Up to 24TB of Raw Storage



Large Form Factor Hard Drive Bay



14th Gen Intel[®] Core[™] Processor



Powered by the Hailo-8 Inferencing Module



4-Stream Perpetual CVEDIA License Included



Milestone Preloaded and License-Ready



5-Year ProSupport Plus NBD On-Site with KYHD







IL-SFFD-M SERIES

IRONLINK® SMALL FORM FACTOR AI NVR FOR MILESTONE

SYSTEM

Operating System:

Windows® 11 Pro Windows® 10/11 IoT Enterprise Ubuntu® Linux 20/22.04

Supported CPU:

14th Gen Intel[®] Core[™] Processors

Memory Configuration:

(2) SODIMM Slots Up to 64GB DDR5 Non-ECC

Embedded Networking:

(2) RJ45 2.5GbE Ports -OR-

(1) RJ45 2.5GbE Port w/DW GPU

Expansion Slots:

(1) PCIe 4.0 x16 LP

(1) PCle 3.0 x4 LP

GPU Support:

Up to (1) Single Wide HH/FL -OR-

(1) Double Wide HH/FL

Security Module:

Trusted Platform Module (TPM) 2.0

MECHANICAL

Form Factor:

Small Tower

Power Supply:

(1) 300W Internal, 92% Efficient, 80 Plus Platinum

Environmental:

Operating Temperature: 50°F ~ 95°F (10°C ~ 35°C)

Non-Operating Temperature: -40°F - 149°F (-40°C - 65°C)

Operating Rel. Humidity: 20% – 80% (non-condensing)

Non-Operating Rel. Humidity: 5% – 95% (non-condensing)

Dimensions (WxDxH):

3.65" x 11.53" x 11.42" (92.6 mm x 292.8 mm x 290 mm)

Weight:

11.86 lb (5.38 kg)

Warranty:

5-Year ProSupport Plus NBD On-Site with KYHD

STORAGE + PORTS

Drive Bays:

(1) Internal Fixed 3.5" SATA

M.2 Slots:

- (2) M.2 slots (2230/2280)
- (1) M.2 slot (2280)
- (1) M.2 slot for Wi-Fi/Bluetooth Card (2230)

Al Accelerator:

(1) M.2 Hailo-8 Inferencing Module

I/O Ports:

FRONT:

- (2) USB 2.0
- (1) USB 3.2
- (1) USB 3.2, Type-C

REAR:

- (4) USB 3.2
- (2) USB 2.0

Video Outputs:

(3) DisplayPort