

IL-R208 SERIES

IRONLINK® 2U RACKMOUNT 8-BAY SERVER

PRODUCT OVERVIEW

The IL-R208 is optimized for demanding network video surveillance applications, and powered by the 3rd Gen Intel® Xeon® Scalable processor for fast and stable performance. These servers support up to 1TB of RAM and offer slots for up to 192TB of HDD storage, all in a 2U rackmount chassis.



KEY FEATURES



Up to 192TB of Raw Storage



Enterprise Class SAS Drives



3rd Gen Intel® Xeon® Scalable Processor



Dedicated Hardware RAID Controller



Redundant Power Supply



5-Year ProSupport NBD On-Site with KYHD



IL-R208 SERIES

IRONLINK® 2U RACKMOUNT 8-BAY SERVER

SYSTEM

Operating System:

Windows® 10/11 IoT Enterprise
Windows® Server 2019/2022
Standard
Ubuntu® Linux 20/22.04

Supported CPU:

(1) 3rd Gen Intel® Xeon®
Scalable

Memory Configuration:

(16) RDIMM Slots
Up to 1TB DDR4 ECC

Embedded Networking:

(2) RJ45 1GbE Ports

Expanded Networking:

(4) RJ45 1GbE Ports (OCP)

Expansion Slots:

(1) PCIe 4.0 x16
(x16 Connector) LP/HL
(1) PCIe 4.0 x4
(x8 Connector) LP/HL

GPU Support:

(1) Single Wide LP/HL

Onboard Management:

iDRAC Enterprise

Security Module:

Trusted Platform Module 2.0

MECHANICAL

Form Factor:

2U Rackmount

Power Supply:

(2) 800W 100-240VAC
Platinum Hot-Swap

Environmental:

Operating Temperature:
50°F ~ 95°F (10°C ~ 35°C)

Non-Operating Temperature:
-40°F – 149°F (-40°C – 65°C)

Operating Rel. Humidity:
10% – 85% (non-condensing)

Non-Operating Rel. Humidity:
10% – 90% (non-condensing)

Dimensions (WxDxH):

18.97" x 27" x 3.41"
(482 mm x 686 mm x 86.8 mm)

Weight:

56 lb (25.40 kg)

Warranty:

5-Year ProSupport NBD
On-Site with KYHD

STORAGE + PORTS

Drive Bays:

(8) Hot-Swap 3.5" SAS

M.2 Slots:

(2) M.2 SSD BOSS slots

Supported RAID Levels:

OS M.2 SSD drives: 0, 1
Data drives: 0, 1, 5, 6, 10

RAID Controller:

PERC H755 8GB

I/O Ports:

FRONT:
(1) USB 2.0

REAR:
(1) USB 3.0
(1) USB 2.0

Video Outputs:

(1) VGA Port Front
(1) VGA Port Rear